


Autonomous Dimming Function for Outdoor luminaires and LED Modules Basic+

SMART TOGETHER. LED Lighting solutions for Municipality , Industry und Commerce

- Lunux luminaires provide the option of autonomous dimming operation.
- During operation, the light level is automatically dimmed to different levels according to a predefined profile (examples below).
- A maximum of 5 dimming steps between 0-100% can be defined.




Description of Operation





- 1. During operation the luminaire counts the runtime between switching on and off and saves this information
- 2. At next operation the saved runtime is used to calculate a virtual midnight point*.
- 3. The dimming points for next operation are then determined relative to this midnight point

*for accurate midnight calculation, the luminaire needs to be switched on in the same offset to sunset as it is switched off to sunrise (e.g. switch on 20 min after sunset and switch off 20 min before sunrise)































































calculated midnight +5

D18: Dimming profile 18















D22: Dimming profile 22























D30: Dimming profile 30




D01: Dimming profile 1

Time	Level
Until +1	100%
+1 to +5	50%
From +5	100%




D02: Dimming profile 2


Time	Level
Until -2	100%
-2 to +5	50%
From +5	100%



D03: Dimming profile 3




D04: Dimming profile 4



D05: Dimming profile 5

Time	Level
Until -2	100%
-2 to +4	60%
From +4	100%




D06: Dimming profile 6

Time	Level
Until -1	100%
-1 to 0	75%
0 to +4	50%
+4 to +5	75%
From +5	100%
100% 75% 50% -1 calculated midnight	+4 +5


D07: Dimming profile 7

Time	Level
Until -2	100%
-2 to +2	60%
From +2	100%




D08: Dimming profile 8

Time	Level
Until -1	100%
-1 to +5	50%
From +5	100%




D09: Dimming profile 9

Time	Level
Until 0	100%
0 to +5	50%
From +5	100%




D10: Dimming profile 10

Time	Level
Until -2	100%
-2 to +6	50%
From +6	100%




D11: Dimming profile 11

Time	Level
Until -1	100%
-1 to +4	50%
From +4	100%




D12: Dimming profile 12

Time	Level
Until 0	100%
0 to +4	50%
From +4	100%




D13: Dimming profile 13

Time	Level
Until -2	100%
-2 to +4	50%
From +4	100%




D14: Dimming profile 14

Time	From
Until -1	100%
-1 to +5	70%
From +5	100%




D15: Dimming profile 15

Time	Level
Until -1	100%
-1 to +5	60%
From +5	100%




D16: Dimming profile 16

Time	Level
Until -2,5	100%
-2,5 to +0,5	75%
+0,5 to +4,5	50%
From +4,5	100%




D17: Dimming profile 17

Time	Level
Until -4	100%
-4 to +5	50%
From +5	100%




D18: Dimming profile 18




D19: Dimming profile 19

Time	Level
Until 0	100%
0 to +5	70%
From +5	100%




D20: Dimming profile 20


Time	Level
Until -1	100%
-1 to +4,5	50%
From +4,5	100%




D21: Dimming profile 21




D22: Dimming profile 22



D23: Dimming profile 23




D24: Dimming profile 24




D25: Dimming profile 25

Time	Level
Until -2	100%
-2 to 0	75%
0 to +4	50%
From +4	100%




D26: Dimming profile 26

Time	Level
Until -3	100%
-3 to -2	65%
-2 to +4	50%
From +4	80%




D27: Dimming profile 27

Time	Level
Until -2	100%
-2 to 0	70%
0 to +5	55%
From +5	100%




D28: Dimming profile 28

Time	Level
Until -2,5	100%
-2,5 to +4,5	50%
From +4,5	100%




D29: Dimming profile 29



D30: Dimming profile 30

Time	Level
Until -1	100%
-1 to +1	50%
+1 to +5	10%
From +5	50%



Thank you

for your attention!

The contents of this presentation are the intellectual property of LUNUX LIGHTING GmbH and are subject to applicable copyright laws.

Any unauthorized use or duplication as well as any kind of forwarding to third parties is not permitted or requires the consent of LUNUX LIGHTING GmbH.

> LUNUX LIGHTING GmbH Zaucheweg 4 04316 Leipzig

Phone +49 (0)341 241 872 0 Fax +49 (0)341 241 872 38 international@lunux-lighting.com www.lunux-lighting.com

