

HELLUX 907

Safety: Optimal illumination of sidewalk and roadway

Reliable: Even lighting without glare

Variable: Modular and adaptable system

Applications areas:

- Attachment to the underside of the handrail handrail



HELLUX

Lunux Lighting GmbH
Zaucheweg 4
04316 Leipzig

Telefon +49 (0)341 241872 0
Telefax +49 (0)341 241872 38


info@lunux-lighting.com
www.lunux-lighting.com

©Lunux Lighting GmbH. The specifications may vary depending on the design. Reserve technical changes. All Rights Reserved.

HELLUX 907



Example of luminous intensity distribution:



LIGHT HOUSING	
Material	Aluminium Strangpress
Colour (powder coating)	DB 703
Mounting type	Attachment to the bottom of the railing handrail
Dimensions (Height x Diameter)	variable
Weight	variable
IP Protection class	IP44
Glas type	PMMA
ILLUMINANT PROPERTIES	
Light source	LED
Optical system	PMMA Lenses asymmetric
Light efficiency	100 lm/W
Colour temperature	3.000K/4.000K
Colour rendering index (RA)	>70
Dimming (Power control)	DALI possible
Rated lifetime at (ta) 30 °C	> 70.000 h
ELECTRICAL PROPERTIES	
Rated power	7W - 14W
Electrical protection class	SK I or SK II
Operating voltage / Frequence	230 V 50 - 60 Hz
Surge protection	4 kV
INSTALLATION REQUIREMENTS	
Application areas	Roads in residential areas, parks, paths, parking areas