

## HELLUX 920

**Safety:** Optimum illumination without glare

**Reliable:** Robust and vandal-proof aluminum housing

**Variable:** Available as single luminaire or continuous line system

**Applications areas:**

- underpasses
- bridges
- tunnel
- stops



HELLUX

**Lunux Lighting GmbH**  
Zaucheweg 4  
04316 Leipzig

Telefon +49 (0)341 241872 0  
Telefax +49 (0)341 241872 38


info@lunux-lighting.com  
www.lunux-lighting.com

©Lunux Lighting GmbH. The specifications may vary depending on the design. Reserve technical changes. All Rights Reserved.

# HELLUX 907



## Example of luminous intensity distribution:



LIGHT HOUSING	
Material	Aluminium Strangpressprofil
Colour (powder coating)	DB 703
Mounting type	Ceiling and wall mounting
Dimensions (Height x Diameter)	LED basic module Length: 1 m, with blind and end pieces
Weight	variable
IP Protection class	Modul IP65
Glas type	PMMA
impact resistance	IK08
ILLUMINANT PROPERTIES	
Light source	LED
Optical system	PMMA Lenses asymmetric available
Light efficiency	up to 127 lm/W
Rated luminous flux	800 - 3600lm
Colour temperature	3.000K/4.000K/
Colour rendering index (RA)	>70
Dimming (Power control)	optional controll phase (50% / 100%), or DALI
Rated lifetime at (ta) 30 °C	60.000 hours L90B10 (after IES LM 80 & TM 21) 100.000 hours L80B10
ELECTRICAL PROPERTIES	
Rated power	7,5W - 30,0W
Electrical protection class	SK II
Operating voltage / Frequence	230 V   50 - 60 Hz
INSTALLATION REQUIREMENTS	
Application areas	Ceiling and wall mounting
FURTHER PROPERTIES	
certification	CE